

## **QUICKFILL MAGAZINES**

**22-152-xxxx**

### **Features and Advantages:**

- Strong injection moulded construction with metal reinforcement
- Meet standard dimensions most frequently used on automated lines
- Very good price/quality ratio
- Not subject to accidental change in width. No wear of moving parts.
- Partition is made of assembled plastic parts
- This system provides a better dimensional stability when strong temperature variations
- All models are supplied with top and bottom metal boards.  
Economical models with plastic boards on request
- Meant for 50 PCB's
- Material : Conductive PS or ABS/PC for plastic parts, galvanized Iron for metal parts
- Slide guide slot Depth : 3,5 mm
- Slide guide slot Pitch : 10 mm
- 2 ways of distribution : in kit with assembling instruction sheet or assembled and ready to use



### **Product specification for PS magazines:**

Material: Conductive PS for the plastic parts and zincification iron for the metal parts  
Usage temperature: up to **60°C**

| Ref.<br>(kit) | Ref.<br>(Assembled) | Dimension<br>(mm) | Min/Max<br>PCB Size | Slide guide slot<br>width | Adjustment<br>system | Top and<br>bottom frame |
|---------------|---------------------|-------------------|---------------------|---------------------------|----------------------|-------------------------|
| 22-152-3060   | 22-162-3060         | 460x400x563       | 50 / 300            | 5                         | Screws               | Metal                   |
| 22-152-4060   | 22-162-4060         | 355x320x563       | 50 / 250            | 5                         | Gear Track           | Metal                   |
| 22-152-6060   | 22-162-6060         | 460x400x563       | 100 / 310           | 5                         | Gear Track           | Metal                   |
| 22-152-7060   | 22-152-7060         | 535x460x570       | 50 / 390            | 5                         | Gear Track           | Metal                   |
| 22-152-8060   | 22-152-8060         | 535x530x570       | 120 / 460           | 5                         | Gear Track           | Metal                   |

### **Product specification for ABS/PC magazines:**

Material: Conductive ABS/PC for the plastic parts and zincification iron for the metal parts  
Usage temperature: up to **110°C**

| Ref.<br>(kit) | Ref.<br>(Assembled) | Dimension<br>(mm) | Min/Max<br>PCB Size | Slide guide<br>slot width | Adjustment<br>system | Top and<br>bottom frame |
|---------------|---------------------|-------------------|---------------------|---------------------------|----------------------|-------------------------|
| 22-152-1120   | 22-162-1120         | 460x400x563       | 50 / 300            | 5                         | Screws               | Metal                   |
| 22-152-2120   | 22-162-2120         | 355x320x563       | 50 / 250            | 5                         | Gear Track           | Metal                   |
| 22-152-3020   | 22-162-3020         | 535x460x570       | 50 / 390            | 5                         | Gear Track           | Metal                   |