EXHELON



The safe and convenient self-retracting lifeline with webbing or galvanised cable





www.zarges.com

Overview of benefits:

- Safety: EXHELON features three fall indicators: One in the carabiner, one in the shock-absorbing lanyard and the ZARGES ZmartCheck.
- Comfort: The ergonomic handle makes it easy to carry.
- Swivel at the top and bottom for excellent freedom of movement.
- Available in lengths of 3, 6, 10 and 15 metres.

EXHELON – galvanised cable or stainless steel cable.

EXHELON features three fall indicators: One in the carabiner, one in the shock-absorbing lanyard and the ZARGES ZmartCheck, an integrated NFC tag for inspections and tests.

The ergonomic handle makes it easy to carry, and the completely redesigned housing offers maximum wearing comfort. The swivel at the top and bottom ensures excellent freedom of movement while keeping the drop distance short.

The device is suitable for persons weighing up to 150 kg and has been tested in accordance with RfU 11.060 for horizontal use with edge protection. It is available in lengths of 3, 6, 10 and 15 metres and in either webbing, galvanised steel or stainless steel. The product includes an aluminium trilock with captive pin on the anchor point side, and an aluminium trilock carabiner on the full-body harness side.



Length m	Weight kg	Carabiner anchor point side	Carabiner, full-body harness side	Standard	Material	Order no.
6.00	3.7	Trilock	Trilock	EN 360	Galvanised steel cable	47853
10.00	4.5	Trilock	Trilock	EN 360	Galvanised steel cable	47854
15.00	6.7	Trilock	Trilock	EN 360	Galvanised steel cable	47855
6.00	3.7	Trilock	Trilock	EN 360	Stainless steel cable	47856
10.00	4.5	Trilock	Trilock	EN 360	Stainless steel cable	47857
15.00	6.7	Trilock	Trilock	EN 360	Stainless steel cable	47858

EXHELON - webbing.

EXHELON features three fall indicators: One in the carabiner, one in the shock-absorbing lanyard and the ZARGES ZmartCheck, an integrated NFC tag for inspections and tests.

The ergonomic handle makes it easy to carry, and the completely redesigned housing offers maximum wearing comfort. The swivel at the top and bottom provides excellent freedom of movement while keeping the drop distance short.

The device is suitable for people weighing up to 150 kg. It is available in lengths of 3, 6, 10 and 15 metres and in either webbing, galvanised steel or stainless steel. The product includes an aluminium trilock with captive pin on the anchor point side, and an aluminium trilock carabiner on the full-body harness side.



Length m	Weight kg	Carabiner anchor point side	Carabiner, full-body harness side	Standard	Order no.
3.00	1.6	Trilock	Trilock	EN 360	47850
3.00	2.0	Rebar hook	Trilock	EN 360	47851
6.00	2.3	Trilock	Trilock	EN 360	47852



FIND OUT MORE



