

WELCOME TO THE NEW ASC 7-SERIES!

MANY SMART FEATURES THAT WILL IMPRESS YOU



WELCOME ASC 7! NICE TO GET TO KNOW YOU BETTER NOW!

The new models come in a completely new design. A new characteristic is the “all-in-view” display, which features digital pressure gauges. Smart: an integrated status bar shows the progress of the process. Another new feature is the expansion to 4 ports for compressor oils and/or UV additives. This eliminates the need to constantly connect and disconnect the cans in the workshop. The option of WiFi connection, which was previously possible via an additional device, is now directly integrated in the 7 series.

ASC 7.3 and ASC 7.3 LE replace our top sellers ASC 6300 G and ASC 6300 G LE. Accordingly, the ASC 7.4 and ASC 7.4 LE models replace the previous ASC 6400 G and ASC 6400 G LE.

Like the 6000 series models, the 7 series appliances are also certified for four refrigerants (R1234yf, R134a, R456A, R513A). Please also order the required connection kit.

Upgrade your workshop and treat your mechanics to a highly efficient and practical and cool looking device!

ASC 7.3

FULLY AUTOMATIC A/C SERVICE UNIT

R134a

R1234yf

R513A/R456A

- Charging cylinder storage capacity: 16 kg
- Vacuum pump capacity: 5 cars/hour
- Wi-Fi on board
- Patented feeding system for fresh oil and UV additive
- Four Oil UV ports accuracy +/-1g
- Used oil drain accuracy +/- 1g
- Automatic vacuum check
- Automatic charging of leak detection additive
- Integrated charging amount database
- Swivel-mount 10" LCD Display
- Heated charging cylinder for high-speed charging, heat-up also possible during the charging and vacuum process
- Special, 8-bearing weighing platform
- Special air conditioner flush function
- Special Hybrid flushing program
- Large recessed tray for tools
- 500 ml used oil container for longer change intervals
- Three USB ports
- Certified for four refrigerants
- Filter performance for 150 kg refrigerant

ASC 7.3
Instruction package
Adapter for non-returnable bottles 1/4" HD

Ref. No. 9103303116
Ref. No. 8889900001
Ref. No. 8885400035

Optional:
Thermal printer

Ref. No. 8885200327



10" LCD DISPLAY

All-in-view rotatable display



WI-FI READY

Integrated wi-fi connection
for easy workflow



4 OIL/UV PORTS

Use different oil types without
changing the bottles

HELPFUL TIPS

Please order the basic ASC unit and your choice of connection kit (you can assign only one of the refrigerants to your device).

CHOOSE THE CONNECTION KIT (APPLICATION FOR R134a, R1234yf, R513A OR R456A).

R134a R513A/R456A

Every kit includes service couplers, oil/UV test bottles and the needed adapters.

Please choose your required hose length.

Connection kit 3 m	Ref. No. 8885500019
Connection kit 5 m	Ref. No. 8885500020
Connection kit 8 m	Ref. No. 8885500021

R1234yf

Every kit includes service couplers, oil/UV test bottles and the needed adapters.

Please choose your required hose length.

Connection kit 3 m	Ref. No. 8885500022
Connection kit 5 m	Ref. No. 8885500023
Connection kit 8 m	Ref. No. 8885500024

R134a R513A/R456A

Bus application with POE oil
Connection kit **8 m** incl. service couplers, POE oil and the needed adapters.

Ref. No. 8885500025

ASC 7.3 LE

FULLY AUTOMATIC LOW EMISSION A/C SERVICE UNIT



R134a
R1234yf
R513A/R456A

- Recycling rate 99,99%
- Charging cylinder storage capacity: 16 kg
- Vacuum pump capacity: 5 cars/hour
- Wi-Fi on board
- Patented feeding system for fresh oil and UV additive
- Four Oil UV ports, accuracy +/-1g
- Used oil drain accuracy +/- 1g
- Automatic vacuum check
- Automatic charging of leak detection additive
- Integrated charging amount database
- Swivel-mount 10" LCD Display
- Heated charging cylinder for high-speed charging, heat-up also possible during the charging and vacuum process
- Special, 8-bearing weighing platform
- Special air conditioner flush function
- Special hybrid flushing program
- Hermitically closed used oil container for the Low Emission concept
- Three USB ports
- Certified for four refrigerants
- Filter performance for 150 kg refrigerant

ASC 7.3 LE

Instruction package

Adapter for non-returnable bottles 1/4" HD

Ref. No. 9103303117

Ref. No. 8889900001

Ref. No. 8885400035

Optional:

Thermal printer

Ref. No. 8885200327



LOW EMISSION

Virtually no refrigerant escaping into the environment



WI-FI READY

Integrated wi-fi connection for easy workflow



4 OIL/UV PORTS

Use different oil types without changing the bottles

HELPFUL TIPS

Please order the basic ASC unit and your choice of connection kit (you can assign only one of the refrigerants to your device).

CHOOSE THE CONNECTION KIT (APPLICATION FOR R134a, R1234yf, R513A OR R456A).

R134a **R513A/R456A**

Every kit includes service couplers, oil/UV test bottles and the needed adapters.

Please choose your required hose length.

Connection kit **3 m** Ref. No. 8885500019
Connection kit **5 m** Ref. No. 8885500020
Connection kit **8 m** Ref. No. 8885500021

R1234yf

Every kit includes service couplers, oil/UV test bottles and the needed adapters.

Please choose your required hose length.

Connection kit **3 m** Ref. No. 8885500022
Connection kit **5 m** Ref. No. 8885500023
Connection kit **8 m** Ref. No. 8885500024

R134a **R513A/R456A**

Bus application with POE oil
Connection kit **8 m** incl. service couplers, POE oil and the needed adapters.

Ref. No. 8885500025

ASC 7.4

FULLY AUTOMATIC, HIGH-VOLUME A/C SERVICE UNIT

R134a

R1234yf

R513A/R456A

- Charging cylinder storage capacity: 28 kg
- Vacuum pump capacity: 192 l/h
- Wi-Fi on board
- Patented feeding system for fresh oil and UV additive
- Four Oil / UV ports, accuracy +/- 1g
- Used oil drain accuracy +/- 1g
- Integrated charging amount database
- Swivel-mount 10" LCD Display
- Heated charging cylinder for high-speed charging, heat-up also possible during the charging and vacuum process
- Special, 8-bearing weighing platform
- Special air conditioner flush function
- Special Hybrid flushing program
- 500 ml used oil container for longer change intervals
- Three USB ports
- Certified for four refrigerants
- Filter performance for 150 kg refrigerant
- Integrated high-performance liquid pump for filling large quantities of refrigerant and/or for filling for special applications of service connections at great heights

ASC 7.4
Instruction package
Adapter for non-returnable bottles 1/4" HD

Ref. No. 9103303118

Ref. No. 8889900001

Ref. No. 8885400035

Optional:

Thermal printer

Ref. No. 8885200327



HIGH VOLUME

For busses, trains, helicopters
and custom applications



WI-FI READY

Integrated wi-fi connection
for easy workflow



10" LCD DISPLAY

All-in-view rotatable display

HELPFUL TIPS

Please order the
basic ASC unit and
your choice of
connection kit (you
can assign only one
of the refrigerants
to your device).

CHOOSE THE CONNECTION KIT (APPLICATION FOR R134a, R1234yf, R513A OR R456A).

R134a **R513A/R456A**

Every kit includes service couplers, oil/UV test bottles
and the needed adapters.

Please choose your required hose length.

Connection kit 3 m	Ref. No. 8885500019
Connection kit 5 m	Ref. No. 8885500020
Connection kit 8 m	Ref. No. 8885500021

R1234yf

Every kit includes service couplers, oil/UV test bottles
and the needed adapters.

Please choose your required hose length.

Connection kit 3 m	Ref. No. 8885500022
Connection kit 5 m	Ref. No. 8885500023
Connection kit 8 m	Ref. No. 8885500024

R134a **R513A/R456A**

Bus application with POE oil
Connection kit **8 m** incl. service couplers,
POE oil and the needed adapters.

Ref. No. 8885500025

ASC 7.4 LE

FULLY AUTOMATIC LOW EMISSION A/C SERVICE UNIT, HIGH VOLUME



R134a
R1234yf
R513A/R456A

- Recycling rate 99,99%
- Charging cylinder storage capacity: 28 kg
- Vacuum pump capacity: 192 l/hour
- Wi-Fi on board
- Patented feeding system for fresh oil and UV additive
- Fully automatic refrigerant recycling, oil and additive management
- Four Oil / UV ports, accuracy +/- 1g
- Used oil drain accuracy +/- 1g
- Automatic charging of leak detection additive
- Integrated charging amount database
- Swivel-mount 10" LCD Display
- Heated charging cylinder for high-speed charging, heat-up also possible during the charging and vacuum process
- Special, 8-bearing weighing platform
- Hermitically closed used oil container for the Low Emission concept
- Three USB ports
- Certified for four refrigerants
- Filter performance for 150 kg refrigerant
- Integrated high-performance liquid pump for filling large quantities of refrigerant and/or for filling for special applications of service connections at great heights



ASC 7.4 LE

Instruction package

Adapter for non-returnable bottles 1/4" HD

Ref. No. 9103303119

Ref. No. 8889900001

Ref. No. 8885400035

Optional:

Thermal printer

Ref. No. 8885200327



LOW EMISSION

Virtually no refrigerant escaping into the environment



WI-FI READY

Integrated wi-fi connection for easy workflow



HIGH VOLUME

For busses, trains, helicopters and custom applications

HELPFUL TIPS

Please order the basic ASC unit and your choice of connection kit (you can assign only one of the refrigerants to your device).

CHOOSE THE CONNECTION KIT (APPLICATION FOR R134a, R1234yf, R513A OR R456A).

R134a **R513A/R456A**

Every kit includes service couplers, oil/UV test bottles and the needed adapters.

Please choose your required hose length.

Connection kit **3 m** Ref. No. 8885500019
Connection kit **5 m** Ref. No. 8885500020
Connection kit **8 m** Ref. No. 8885500021

R1234yf

Every kit includes service couplers, oil/UV test bottles and the needed adapters.

Please choose your required hose length.

Connection kit **3 m** Ref. No. 8885500022
Connection kit **5 m** Ref. No. 8885500023
Connection kit **8 m** Ref. No. 8885500024

R134a **R513A/R456A**

Bus application with POE oil
Connection kit **8 m** incl. service couplers, POE oil and the needed adapters.

Ref. No. 8885500025

WAECO Germany WSE GmbH
Hollefeldstraße 63
48282 Emsdetten



info@waeco.com
waeco.com

CEMEA

GERMANY & AUSTRIA

Tel +49 (0) 2572 879-0
sales.de@waeco.com

BELGIUM

Tel +32 2 3598040
sales.be@waeco.com

NETHERLANDS

Tel +31 76 5029000
sales.nl@waeco.com

UNITED ARAB EMIRATES

Tel +971 4 883 3858
sales.de@waeco.com

NORTHERN EUROPE

NORWAY

Tel +47 33428450
sales.no@waeco.com

SWEDEN

Tel +46 31 7341100
sales.se@waeco.com

DENMARK

Tel +45 75585966
sales.dk@waeco.com

FINLAND

Tel +358 20 7413220
sales.fi@waeco.com

SOUTH EUROPE

ITALY

Tel +39 0543 754901
sales.it@waeco.com

SPAIN

Tel +34 91 833 6089
sales.es@waeco.com

PORTUGAL

Tel +351 219 244 173
sales.pt@waeco.com

FRANCE

Tel +33 3 44 63 35 00
sales.fr@waeco.com

EASTERN EUROPE

HUNGARY

Tel +36 1 468 4400
sales.pl@waeco.com

SLOVAKIA

Tel +421 2 45 529 680
sales.pl@waeco.com

POLAND & CZECH REPUBLIC

Tel +48 22 414 3200
sales.pl@waeco.com

ROMANIA

Tel +48 22 414 3200
sales.pl@waeco.com

UNITED KINGDOM

UNITED KINGDOM

Tel +44 344 626 0133
sales.uk@waeco.com

**FOR ENQUIRIES FROM OTHER REGIONS AND FOR ALL CROSS-COUNTRY ENQUIRIES,
PLEASE CONTACT: INFO@WAECO.COM**