

Groep 965 / RVS Expansiestukken laseinden



Design Pressure: 2.5 barg
Design Temperature: 550 degC
Bellows material: 321SS

Artikel	DN	Materiaal laseinden	L (mm)	Ln (mm)	s (mm)	OD (mm)
	MM (IN)	mm	mm	mm	@20°C/bar	@100°C/bar
965-01-032E	DN 32 (1.1/4")	S235	205	130	3.2	37
965-01-040E	DN 40 (1.1/2")	S235	205	139	3.2	47
965-01-050E	DN 50 (2")	S235	245	150	3.6	58
965-01-065E	DN 65 (2.1/2")	S235	245	157	3.6	74
965-01-080E	DN 80 (3")	S235	245	158	4	86.5
965-01-100E	DN 100 (4")	S235	245	147	4.5	111
965-01-125E	DN 125 (5")	S235	245	148	5	136
965-01-150E	DN 150 (6")	S235	245	141	5	164
965-01-200E	DN 200 8")	S235	245	141	4.5	219.1
965-01-250E	DN 250 (10")	S235	245	131	5.6	273
965-01-300E	DN 300 (12")	S235	295	177	6	323.9
965-01-350E	DN 350 (14")	S235	295	189	6	355.6
965-01-400E	DN 400 (16")	S235	295	199	8	406.4
965-01-500E	DN 500 (18")	S235	295	183	6	508

