



HOW WE DELIVER PEACE OF MIND WITH THE BEST SEALING SOLUTIONS FOR PUMPS, SHIPS, AND TIDAL TURBINES

COMPANY INTRODUCTION

EVER SINCE ITS ESTABLISHMENT IN 1856, LAGERSMIT HAS MET THE NEEDS OF MANY SECTORS OF INDUSTRY THAT CALL FOR ABSOLUTE RELIABILITY. THANKS TO THIS HERITAGE AND WITH MORE THAN 45,000 SEALS DELIVERED, WE HAVE GAINED THE KNOWLEDGE, RESOURCES, AND CAPACITY TO DEVELOP SECURE, PREDICTABLE SEALS FOR THE INDUSTRY THAT KEEP GOING – BOTH NOW AND IN THE FUTURE.

It's important that all sealing components are of the highest quality and are perfectly compatible with each other. At the production facility at our headquarters in the Netherlands, we make sure that our Liquidyne pump shaft seals and Supreme® propulsion seals meet these high standards – adding quality and reliability to your operation. Lagersmit currently delivers Peace of Mind to a vast network of pump manufacturers, (petro)chemical and energy companies. This brochure features the Real Stories of a few of these customers.

Believing that there's always room for improvement, we keep developing new ideas for your applications and deliver the best sealing solutions according to our Modular, Made-to-Measure philosophy.

Our dedicated service network covers your needs 24 hours a day, 7 days a week, worldwide.

1856

DUNDED



BASED IN THE NETHERLANDS



24/7 WORLDWIDE SERVICE &



DELIVERED OVER 45.000 SEALS LIQUIDYNE® PUMP SHAFT SEAL VS...

SIASIAL SIAL

Released in 1983, the Liquidyne pump shaft seal was initially intended for heavy-duty dredge pumps and is the next step for gland packing and the alternative of a mechanical seal. Thanks to its robust design, the seal can handle above-average axial and radial play. It is suitable for pumps that have to deal with severe shocks and vibrations, incorrect alignment, and abrasive media. The Liquidyne increases the pump's lifetime and leads to a longer mean time between maintenance (MTBM) thanks to its robustness. Condition monitoring adds predictability and secures your operation.

...VS GLAND PACKING

Summarised top advantages Liquidyne versus gland packing:

- Condition monitoring ensures you can plan maintenance efficiently, optimise MTBM, reduce costs, and minimise the risk of sudden pump failure;
- Energy savings due to less friction and minimised heat development;
- Safe workplace the floor is kept dry, and no adjustments are required during operation;
- Easy to maintain no other tasks required besides condition monitoring.

...VS MECHANICAL SEAL

Summarised main advantages Liquidyne versus mechanical seal:

- Predictable lifetime: condition monitoring minimises the risk of sudden pump failure
- Optimised cost of ownership thanks to the possibility of ordering spare parts, energy savings, and easy maintenance
- The Liquidyne has a robust seal design, making it virtually non-sensitive for abrasive media

GLAND PACKING

COMPARED WITH GLAND PACKING, THE LIQUIDYNE SEAL IS THE NEXT STEP FOR YOUR OPERATION AND OFFERS THE FOLLOWING ADVANTAGES:

PREDICTABLE LIFE TIME

The Liquidyne offers a simple yet effective way of condition monitoring using the drain flow. This means you can verify the seal condition at any time and also predict the remaining lifetime of the seal. It optimises the mean time between maintenance, minimises the risk of sudden pump failure, and minimises the total cost of ownership. The Liquidyne makes condition monitoring easy. Have a look at our 'Real Story: Predicting lifetime' on page 16 for more information.

ENERGY SAVINGS

The Liquidyne seal uses a lubrication film between the lip seals and shaft sleeve to ensure the lowest possible friction and minimal heat development, minimising energy consumption and saving costs.

SAFE WORK PLACE

The drain line of the Liquidyne seal keeps the factory floor dry, as no water sprays from the seal are needed to lubricate the seal. This ensures a clean, dry, and a non-slippery factory floor, keeping your workers safe. As no adjustments have to made to the seal during operations, engineers do not have to perform maintenance on rotating equipment – this avoids any unnecessary risks.

EASY TO MAINTAIN

Once the Liquidyne is installed, the only task required during operation is to check the flow from the Liquidyne drain as a means of condition monitoring. The Liquidyne does not need to be adjusted during the operation of the seal, keeping your pump safely running.

IQUIDYNE PUMP SHAFT SEAL

MECHANICAL SEAL

THE LIQUIDYNE SEAL IS A BETTER ALTERNATIVE TO A MECHANICAL SEAL AND OFFERS THE FOLLOWING ADVANTAGES:

PREDICTABLE LIFE TIME

The Liquidyne operates while being condition monitored. This feature ensures Peace of Mind, as it allows the operator to observe the trend line of the flow from the drain. It also features a timely notification when the drain flow is at 20% (instead of a sudden failure of a seal), so you can plan maintenance. Have a look at our 'Real Story: Predicting lifetime' on page 16 for more information.

OPTIMISED COST OF OWNERSHIP


The Liquidyne is economically attractive because of the possibility to order spare parts. Usual maintenance calls for the whole seal to be replaced – not with the Liquidyne. A typical initial maintenance would involve changing the soft wear parts only. Just imagine the cost savings: using the Liquidyne means you only change the actual wear parts!

Energy consumption is minimised because the seal uses a lubrication film between the lip seals and shaft sleeve, ensuring the lowest possible friction and minimal heat development. Besides spare parts and savings on the energy consumption, the seal is also easy to maintain. The only maintenance required during operation is to check the drain flow from the Liquidyne as a means of condition monitoring, which saves valuable working time for staff.


ROBUST SEAL DESIGN

Initially developed for heavy-duty dredge pumps, the seal's robust design plus the use of lip seals means it's virtually non-sensitive to abrasive media.

The axial positioning on the shaft is no longer a precision job thanks to the lip seals. Air traps, sudden drops or spikes in pressure, and vibrations aren't a direct reason for the failure of the Liquidyne seal. As the Liquidyne is a radial seal, the positioning on the shaft sleeve is always on point. The Liquidyne seal can handle above-average axial and radial play compared with a mechanical seal.



SELECT YOUR PUMP



REAL QUOTE: **NOURYON INDUSTRIAL CHEMICALS**

Nouryon Industrial Chemicals (formerly AkzoNobel) has several Liquidyne® seals installed on their circulation pumps in their Salt factory. The seal has to withstand tough working conditions, such as with salt water or at high temperatures over 100 degrees Celsius.

Customer Support

The Liquidyne seal is robust and incredibly tough, with the biggest advantage being that the degree of wear and tear of a seal is measurable. This condition monitoring enables us to better plan maintenance and coordinate related activities with production. The Liquidyne has been installed for six years now: it's had no maintenance, and it hasn't failed once so far.

The Liquidyne is economically attractive: after more than six years, the seal is still in such a good condition that you'll only need to replace a few parts of the seal instead of purchasing a completely new seal.

HARMJAN SPAAN
Supervisor Maintenance (rotating) – Nouryon

SEALING MATCH

more information about the Liquidyne seals, see section -Liquidyne pump shaft seals- starting from page 12

	LIQUIDYNE 2-STAGE	LIQUIDYNE 2-TG	LIQUIDYNE 3-STAGE	LIQUIDYNE 3-TG	LIQUIDYNE 3-STAGE	LIQUIDYNE LDS
PUMP					VACUUM	
Vertical sump pumps • Cantilever pump	⊘		₹			
Deepwell pumps					✓	②
Slurry pumps			\bigcirc			⊘
Self-priming centrifugal pumps	⊘	•	⊘	⊘	⊘	②
Diffuser pumps • Vertical • Water • Oil & Gas	⊘	\bigcirc	⊘	⊘	⊘	⊘
Booster pumps	⊘	₹	⊘	✓	✓	②
Split case pumps	⊘	₹	₹	₹	₹	②
Concrete volute pump Vertical Axial Between Bearing	\bigcirc	⊘	⊘	⊘	⊘	⊘
Sewage pumps • Waste water			⊘			⊘
Vertical suspended pumps FirefightingCool waterIrrigation drainage	⊘	⊘	⊘	⊘	⊘	⊘
Axial pumps		\checkmark	\bigcirc	\bigcirc	\bigcirc	\bigcirc
Fish-friendly pumps	⊘	✓	✓	✓	✓	⊘

PREDICTING SEAL'S LIFETIME

KEEPS YOU GOING

PUMP SHAFT

REAL STORY: **STORK**

As a pump manufacturer with a rich and long history, we have ample experience in designing pumps. The shaft seal is an essential part of our pumps. In the past, Stork Pumps often used compression gland packing and mechanical seals.

As recently as 2018, we converted a compression gland packing into a water-lubricated Liquidyne[®] seal for a pumping station pump. This involved a Stork pump from 1969 equipped with a grease-lubricated compression gland packing. The Water Board (Waterschap) prescribed a water-lubricated lip seal, in part because of its target to eliminate the use of grease in surface water. As a pump manufacturer, we always carefully weigh up our options. We have chosen a pump shaft seal from Lagersmit, partially because of our positive previous experiences with the quality of products delivered, the service offered, and options for joint, customer-specific engineered solutions.

Adjustments have been made to the pump parts, and the Liquidyne seal – delivered on time – has been installed. The pump, complete with the new Liquidyne seal, was then successfully commissioned and tested in the pumping station. We have positive experiences working with Lagersmit and regard them as a reliable, high-quality partner for our pump shaft seals.

GEERT HOEFLAAK
Business Developer- Stork

Account Manager

LIQUIDYNE® PUMP SHAFT SEALS

AS A MANUFACTURER AND SUPPLIER OF THE LIQUIDYNE PUMP SHAFT SEAL WE HAVE A STRONG FOCUS ON INCREASING THE MEAN TIME BETWEEN MAINTENANCE (MTBM ROTATING EQUIPMENT AND AT THE SAME TIME LOWERING MAINTENANCE COSTS.

How the Liquidyne works in a nutshell

The (water) lubricated Liquidyne lip seals ru over a partially grooved bush placed over the pump shaft. The helical shape of the grooves and peripheral velocity of the bus create water flow between the grooves and the lip seal.

Predictable lifetime


One of the main benefits of the <u>Liquidyne</u> is that the condition monitoring function is not just to simply monitor t condition of the seal, but it also creates predictable lifetime. How? Over time the grooves on the bush gradually wear down. Less water is transported over the bush and the amount of water leaving the drain decreases. When the drain flow is at 20% of the initial flow, maintenance needs to be planned.

By keeping track of this drain flow you can plan maintenance more efficiently minimising the risk sudden pump failure, optimise mean time between maintenance and reduce costs.

The Liquidyne seal is environmentally friendly due to the following characteristics:

- Energy savings (Water) lubricated
- Other benefits:
- Increased reliability due to robust seal design (see also our Real Story from Nouryon Industrial Chemicals in section -select your pump- starting from page 8)
- Environment Health Safety: No leakage on the floor, safe and clean working environment
- Optional design: the Liquidyne can be executed with divisible housing parts. Ask for details.

LIQUIDYNE® 2-STAGE



STANDARD DESIGN



How it works

BENEFITS



medium to lubricate the seal.



The Liquidyne 2-Stage is the standard design of the Liquidyne

range. This seal is used in pumps that process relatively clear

media that may contain abrasive particles that are no larger

than 100 microns. The Liquidyne 2-Stage design uses the proces





















How it works

The Liquidyne 3-Stage Vacuum is specially designed to hold a water column up to eight metres when the pump is at a standstill. The vacuum module also prevents air leakage through the seal into the pump if the pressure inside the pump is lower than the atmospheric pressure.


- Predictable lifetime due to condition monitoring The Liquidyne 2-Stage advantages plus:
- Low power consumption
- Maximised maintenance interval
- Hard Metal Layer (HML) coating for extra durable grooved liners
- No external flush needed
- Optional design: the Liquidyne can be designed with divisible housing parts. Ask for more details.

OPTIONAL: LIQUIDYNE® 2-TG

As this application is typically used on low-pressure pumps, the liner does not feature a grooved surface but a smooth, flat surface.



LIQUIDYNE® 3-STAGE VACUUM
















How it works

Lagersmit developed this Liquidyne 3-Stage seal especially for pumps with a pump medium polluted with abrasive media. This Liquidyne seals the pump and uses an external flush to lubricate, cool, and clean the seal, while the drain flow enables the condition monitoring.

ADDITIONAL BENEFITS

- Suitable for dry start-up of the pump
- Retains pump medium up to eight metres

LIQUIDYNE® 3-STAGE



















ADDITIONAL BENEFITS

OPTIONAL: LIQUIDYNE® 3-TG


flat surface.

The Liquidyne 2-Stage advantages plus:

As this application is typically used on low-pressure pumps, the liner does not feature a grooved surface but a smooth,

- Robust seal design
- Dirt retaining module

LIQUIDYNE® LDS

















How it works

and agressive media. It seals off the pump and uses an external flush to lubricate, cool, and clean the seal. The flush flows through the seal as well as towards the pump. This ensures that the pump medium is kept away from the seal to create the most durable solution. The drain flow enables condition monitoring.

The Liquidyne 2-Stage advantages plus:

Suitable for dry start-up

The Liquidyne LDS design is used in pumps that process polluted

ADDITIONAL BENEFITS

- Most durable solution

EAL CUSTOM DESIGN: **LIQUIDYNE HYBRID SEAL**

We're always up for a new challenge! Our R&D team enjoys exchanging ideas and creating the sealing solution you need. Read more about our Liquidyne® Hybrid seal that we have developed.

A special Hybrid (combination of a Supreme® and Liquidyne)

Hvbrid seal

has been manufactured for cooling-water pumps for nuclear reactors. A Supreme seal is installed in the cooling-water pump's drive mechanism and used to keep out lubricant. In addition, a Liquidyne is used to ensure the water is retained in the

How it works

cooling-water pump.

The Liquidyne Hybrid is specially designed for concrete volute pumps that are designed with a grease-lubricated roller bearing at the bottom. The Liquidyne Hybrid system consists of two parts: the pump shaft seal is used to seal the pump shaft of a vertical pump, while the bearing seal protects the pump bearing and its grease environment.

The seals are placed inline over the pump shaft. The pump shaft seal is mounted on the pump cover or housing part of an inflatable seal, whereas the bearing seal is mounted directly on the bearing housing.



The bearing seal – known as Supreme® – is a grease-lubricated seal unit. A bearing seal is placed in order to prevent water or dirt from entering the bearing housing on both sides.

The pump shaft seal is a water-flushed sealing system known as Liquidyne LDS. This system is particularly able to withstand high and variable loads caused by circumferential velocities and pressure differences. In addition, thanks to its flexible lip seals, the pump shaft seal can continue to function at its best even with axial movement.

Design

- Pump shaft seal module
- Pressure-reducing module
- Inflatable seals
- Bearing seal module
- Uses external flush to:
- Clean
- Cool the seal
- Active flow to pump side

If you want to know more about our custom-designed sealing solutions, please get in touch with our experts by sending an e-mail to industry@lagersmit.com!





ENERGY SAVINGS



YOUR PEACE OF MIND

REAL ENERGY SAVINGS: **SABIC**

On SABIC Utilities' site in Bergen op Zoom, we have changed the gland packings of the 1 MW cooling water pumps into Liquidyne seals. Replacing the shaft seal led to the following results for SABIC.

Costs

Due to the minimized friction of the Liquidyne seal, the pump consumes **12.6%** less power.

Availability

Pump availability increased into **99.5%**, meaning an improvement of **53%**.

Reliability

The lifetime of the Liquidyne seal was extended to between six and eight years.

Environment Health Safety

No maintenance and adjusting needed during operation.
No leakage - safe and clean working environment.

REAL STORY: **PREDICTING LIFETIME**

PREDICTING LIFETIME

Whether it's a dredge operation or an industrial water process, work goes on – day and night, worldwide. Condition monitoring enables you to keep track of your seal's performance and plan maintenance in time, enabling a predictable lifetime and minimising the risk of for example sudden failures. You can measure your seal's performance in different ways, ranging from a simple manual operation with a bucket and timer to a completely automated approach with a programmable logic controller (PLC).

MANUAL CONDITION MONITORING

If you want to manually monitor the seal's condition, all you need is a bucket and stopwatch. The water from the Liquidyne® is eventually transported from the pump side to the drain side of the seal. At this point, you can use a bucket to collect the drain flow for a period of time (like 60 seconds) and record how much water you collected.

Our specialists are often asked exactly what you should take notice of when checking the condition of the seal. Most important is to measure the following within fixed time intervals:


- Water inflow and outflow (litres/hour)
- Temperature difference between inflowing and outflowing water

HOW TO MONITOR THE CONDITION OF THE SEAL WITH THE FLOW METER

A digital flow meter is used to measure the rate of flow of liquids, in this case water. For Liquidyne pumping applications, Lagersmit offers a range of approved, fully digital flow meters. By installing the non-mechanical flow meter in a pipeline from the pump, the flow is logged without disrupting the flow. The data can be logged locally at the pump site or, if you have a more advanced approach, in your data management system (PLC). If logged, you will see a similar graph to figure 1.

The state of the grooved bush is measured based on the flow. Due to the wear of the grooves on the grooved bush, the flow decreases over time. The lip seal will also have more contact with the running surface and allows less water to be transported over the bush. The water flow towards the drain decreases, and as a result the drain flow decreases.

Recording the drain flow from the moment the seal was taken into use allows for maintenance to be scheduled more efficiently and the maintenance interval to be maximised. When the drain flow is at 20% of the initial drain flow, you can plan maintenance.



The most advanced way to monitor the condition of your seal is to connect the digital flow meter to a PLC.


SUITABLE FOR WHICH LIQUIDYNE SEALS?

The Liquidyne 3-stage is used as an example, but the digital flow meter can be applied on all Liquidyne seals.

This means you can apply the flow meters on Liquidynes for dredge pumps, industrial (cooling) water or other pumps, jet pumps, gland pumps, and process pumps.

If you'd like to know more information about the digital flow meter, have a look at page 19.

16 PREDICTING LIFETIME



FLOW METER



Monitoring the drain

Lagersmit offers the next step in ensuring a secure pump operation thanks to selected digital flow meters, which simplify the task of monitoring of the Liquidyne® seal and the pump condition.


How it works

By installing a non-mechanical flow meter in a pipeline from the pump, the flow is logged without disrupting the flow. The data can be logged in your data management system or locally at the pump site. Read our Real Story: Predicting lifetime on page 18 for more information about how you can keep track of your seal's performance and enable a predictable lifetime.

BENEFITS

- Maintenance can be planned and intervals maximised
- Better control and accuracy of flush and drain
- Applicable to all Liquidyne seals

CLOSED LOOP LUBRICATION UNIT (CLLU)



The Liquidyne is a sealing solution that needs to be flushed during heavy-duty operations, such as when dealing with abrasive media. For situations in which no flush supply is present, Lagersmit has developed a Closed Loop Lubrication Unit (CLLU) to circulate external flush medium. Circulating the flushing medium minimises the total consumption of the seal and increases the durability of the Liquidyne seal, as flush water is filtered. The system can be Made-to-Measure for your application and available space. The CLLU will monitor the seal's performance and provide an alarm when maintenance needs to be planned.

THE CLLU CAN BE APPLIED TO:

- Liquidyne 3-Stage
- Liquidyne 3-Stage Vacuum
- Liquidyne 3-TG



REAL SERVICE

SERVICE

Our service engineers are your seal experts and can assist with installing and overhauling a Liquidyne seal on location. Every engineer is specifically trained to ensure optimal quality. Their focus ranges from installation to supervision, and from troubleshooting to regular maintenance.

After every service job, we carefully store all relevant information to ensure your Peace of Mind during the next maintenance job.

This enables you to protect your core business, 24/7, worldwide.

- Commissioning
- Troubleshooting
- Installation
- Retrofit
- Maintenance

service@lagersmit.com +31 (0)88 0216 300 GET IN TOUCH

CONTACT

Get in touch with our experts for more information!

industry@lagersmit.com

+31 (0)88 0216 200

LAGERSMIT.COM



