

## Rain Gauge with 200 cm<sup>2</sup>, 400 cm<sup>2</sup> & 1000 cm<sup>2</sup> funnel size





200 cm<sup>2</sup>

400 cm<sup>2</sup>

## **The Rain Gauge**

The Rain Gauge measures the amount of rain, snow or hail that falls on the ground. It functions as a "tipping bucket": the water passes through the funnel and is collected by a calibrated bucket. After a preset amount of precipitation, the bucket tips over, and automatically sends a signal to an external data acquisition system.

- The design of the rain gauge prevents rain from splashing in and out, as recommended by the World Meteorological Organization.
- A protection filter prevents leaves from falling inside the collector. The shape and size of the filter are designed to reduce possible clogging.
- The optional heating system makes sure snow or hail can be measured as well, while preventing evaporation of the water.

## **Technical Specifications of the Rain Gauge**

Feature	Specification
Sensor type	Anodised aluminium tipping bucket with double magnetic contacts
Collecting funnel	Circular 1000 cm <sup>2</sup> Circular 400 cm <sup>2</sup> Circular 200 cm <sup>2</sup>
Resolution	0.2 mm (0.1 mm on demand with 1000 cm² models)
Accuracy	200 cm <sup>2</sup> : 1 tipping or better than 2% at an intensity of 24mm/h 400-1,000 cm <sup>2</sup> : 1 tipping or better than 1% at an intensity of 24mm/h
Range	0 - 300 mm/h
Levelling	Set of bucket with level
Electric output	200 cm²: Single contact 400/1,000cm²: Double contact (single contact on demand)
Working temperature	From -30°C to +70°C (with heater)
Recalibration	Annual check recommended
Maintenance	Periodic cleaning of the calibrated funnel and filter
Dimensions	h: 860 mm - Ø 430mm h: 480 mm - Ø 230mm h: 300 mm - Ø 160mm
Weight	15 kg (17 kg heated ver.) 3.5 kg (4,5 kg heated ver.) 0.85 kg (1,85 kg heated ver.)

## Technical specifications of the heating system (optional)

Feature	Specification
Power supply	24 Vac
Power consumption	450W @ 24Vac model with 1000 cm² collecting funnel 60 W @ 24 Vac model with 400 cm² collecting funnel 60 W @ 24 Vac or 15 W @ 12 Vac model with 200 cm² collecting funnel
Trigger temperature	Ranging from 4°C e 6°C

