OptiCam HD-300

- Portable borehole camera
- Electric winch
- 300m Kevlar cable
- Dual view HD camera
- Waterproof 50 bar
- High power LEDs







Dual view camera

Adjustable skid

The OptiCam HD-300 portable borehole camera system consists of a portable electric winch, a control unit and a dedicated downhole dual-lens camera. The control unit is equipped with 10500mA li-ion battery. Dual view (side/down) rotation camera head in 304 stainless steel casing, 6 bottom and 6 side high-brightness LEDs. The control system has its own depth sensor, which can display the depth measurement in real time with a built-in thermometer and compass.

Camera:

- Diameter ø45mm x 422mm
- Dual view (side/down)
- 360° Pan rotation
- 1,3 Megapixel HD sensor
- 6 LEDs for side camera
- 6 LEDs for down camera
- Lens window sapphire glass
- Waterproof 50 bar
- Adjustable diameter skid

DVR Control unit:

- 13 inch HD color display
- Digital recorder (video resolution 720p)
- USB wireless keyboard
- Camera rotation control
- Winch operation (speed , up and down)
- Li-Ion battery 10Ah and 110-230VAC input for electrical winch

Cable Reel:

- Winding speed 0~20m/min
- Ø8mm Kevlar cable, length: 300m (option 100-400m)
- Power Supply: 110 230VAC

Opticon Benelux Naarden BV - Kobaltstraat 5B - 1411 AM Naarden - Netherlands Tel: +31 (0) 35 69 53 991 - www.opticonbnl.com - info@opticonbnl.com

OPTICON Benelux