

cushion pack

packaging padding machines

Space-saving storage of cartons and just-in-time production of package padding reduce storage costs.

*Give your waste cardboard
a second life!*

NEW SERIE S3!
ergonomic and safer



energy efficiency class IE3



cushion pack

ecologically beneficial packaging

cushion pack package padding machines
turn small quantities of old cardboard into
lots of packaging material within a short time.



self-made ● low-priced ● ecologically beneficial



cushion pack

padding material or flat padding mats
special designs

*Give your waste cardboard
a second life!*



stripes 4mm
DIN66399/1-2



pourable chips
8x40-200mm



flat padding mats



padding material

cushion pack

CP 333 NTi S2
table top model



nergie efficiency class IE3



The new table-top machine
for which the reward is the journey...



the reward - to consistently put an
environmentally-friendly idea into practice.

**Explore new avenues with the environmentally friendly,
energy-efficient CP 333 NTi S2 table-top machine!**

Not only is the packaging padding machine
CP 333 NTi S2 produces environmentally friendly packaging padding from
old, used cardboard boxes, with its new design it consistently further devel-
ops this basic ecological concept.

For example, the body of the CP 333 NTi S2 is made of 70 % sustainable
raw materials (laminated board - plywood and MDF panels) and the machi-
ne is produced exclusively with renewable energy resources.

Produced with 100 % renewable energy resources
Made of 70 % sustainable raw materials

cushion pack

*Give your
waste cardboard
a second life!*

flat padding mats
simple controls
gearbox motor with inverter
table top model



The simple controls and the drive technology with inverter comply with the latest EU requirements, which are obligatory Europe-wide.



easy cleaning with
a vacuum cleaner



nergie efficiency class IE3



Technical data

CP 333 NTi S2

Loading width - cardboard size	endless
Cutting width - padding	320 mm
inlet height	12 mm
Production output	1 - 2 m³/h
Throughput rate	10 m/min
Motor capacity	0,55 KW
Main voltage	230V/50-60Hz
Noise Emission no-load	59 dB(A)
Noise Emission operating cycle	65 dB(A)
Dimensions H x W x D mm	460x580x620
Weight	78 Kg



cushion pack

CP 316/320 S3i
single phase models

NEW SERIE S3!
ergonomic and safer

Energy-efficient drive technology
thanks to the use of
a frequency converter:

high motor torque
even at low speeds,
high dynamics,
high degree of efficiency
and above all energy efficiency!



*Give your
waste cardboard
a second life!*

Up to 30 % energy saving with same output!
All this is possible with the new drives at **cushion pack!**

self-made packaging padding material



cushion pack



nergie efficiency class IE3



NEW SERIE S3!
ergonomic and safer

padding material or flat padding mats
simple controls
gearbox motor with inverter
built-in dust extraction device
(except CP 333/316 S3i)



- operator-friendly feeding of cartons
- circuit-breaker according to IEC/EN 60204-1

standard dust extraction device
built into all models
(except CP 333/316 S3i)

	CP 316 S3i	CP 320 S3i*
·	endless	endless
	320 mm	320 mm
(	12 mm	15 mm
i	1 - 2 m³/h	2 - 3 m³/h
	870mm	870mm
\	10 m/min	12 m/min
·	0,75 KW	0,75 KW
	230V/50-60cps	230V/50-60cps
	60 dB(A)	60 dB(A)
	68 dB(A)	68 dB(A)
	1010x660x660	1010x660x660
\	98 Kg	110 Kg

cushion pack

CP 422 S3i single phase or 3 Phase
padding size 42cm

*Give your
waste cardboard
a second life!*



nergie efficiency class IE3



NEW SERIE S3!
ergonomic and safer

**of course with the well-known
cushion pack - standards**

self-made packaging padding material



cushion pack

NEW SERIE S3!
ergonomic and safer

simple controls
padded or flat material
3 Phase or 1 Phase available
built-in dust extraction device
padding material up to 42cm width



controls and circuit-breaker
according to IEC/EN 60204-1

standard dust
extraction device
built into all models
(except CP 333/316 S3i)



Technical data	CP 422 S3i	CP 422 S3i 3Ph
Loading width - cardboard size	endless	endless
Cutting width - padding	420 mm	420 mm
inlet height	18 mm	18 mm
Production output	4 - 6 m ³ /h	4- 6 m ³ /h
working height	870mm	870mm
Throughput rate	13 m/min	13 m/min
Motor capacity	1,5 KW 1Ph	1,5 KW 3Ph
Main voltage	230V/50-60cps	400V/50-60cps
Noise Emission no-load	60 dB(A)	60 dB(A)
Noise Emission operating cycle	68 dB(A)	68 dB(A)
Dimensions H x W x D mm	1010x660x660	1010x660x660
Weight	125 Kg	125 Kg

cushion pack

CP 428 S2i / CP 430 S2i

3 Phase Models / padding size 42cm

*Give your
waste cardboard
a second life!*

e

nergie efficiency class IE3



self-made packaging padding material



cushion pack



speed control
high production output
inverter technology inside
powerfull gearbox motors
built-in dust extraction device
padding material or flat padding mats



padding material



flat padding mats

Technical data	CP 428 S2i	CP 430 S2i
Loading width - cardboard size	endless	endless
Cutting width - padding	420 mm	420 mm
inlet height	20 mm	20 mm
Production output	6 -9 m ³ /h	7-10 m ³ /h
working height	890mm	890mm
Throughput rate	12/14 m/min	14/16 m/min
Motor capacity	3,0 KW 3Ph	4,0 KW 3Ph
Main voltage	400V/50-60cps	400V/50-60cps
Noise Emission no-load	61 dB(A)	64 dB(A)
Noise Emission operating cycle	71 dB(A)	78 dB(A)
Dimensions H x W x D mm	1100x750x800	1100x750x800
Weight	252Kg	295 Kg

cushion pack

ChipMaker CP 424 CMi

*Give your
waste cardboard
a second life!*

The new ChipMaker CP 424 CMi produces
pourable cushioning chips for packaging
made out of used cardboard boxes.



device for absorbing
the chips

ChipMaker - self-made packaging chips

pourable cushioning chips for packaging
made out of used cardboard boxes by yourself



cushion pack



invertertechnology inside
pourable cushioning chips
device for absorbing the chips



The direction of insertion of
the cardboard box
determines the length of
the cushioning chip!
chip size approx. 8x40-200mm



Technical data

	CP 424 CMI
Loading width - cardboard size	endless
Cutting width	420 mm
inlet height	15 mm
Throughput rate	12 m/min
Motor capacity	1,1 KW 1Ph
Main voltage	230V/50-60cps
Noise Emission no-load	61 dB(A)
Noise Emission operating cycle	75 dB(A)
Dimensions H x W x D mm	1400x750x800
Weight	185 Kg

*add. device for absorbing

cushion pack

packaging padding machines

*Give your waste cardboard
a second life!*

Model	Voltage	Watt	Inlet height	Cutting width	Speed	Volume	Weight	Dust exhaust	Loudness	Size
CP 333 Nti	240V/1	0,55 kw	12 mm	323 mm	10 m/min	1-2 m³/h	78 kg	No	59-65 dB(A)	460 x 580 x 620 mm
CP 316 S3i	240V/1	0,75 kw	12 mm	320 mm	10 m/min	1-2 m³/h	92 kg	No	60-68 dB(A)	1010 x 660 x 660 mm
CP 320 S3i	240V/1	0,75 kw	15 mm	320 mm	12 m/min	2-3 m³/h	110 kg	Yes	60-68 dB(A)	1010 x 660 x 660 mm
CP 422 S3i/240	240V/1	1,5 kw	18 mm	420 mm	13 m/min	4-6 m³/h	125 kg	Yes	60-68 dB(A)	1010 x 660 x 660 mm
CP 422 S3i/400	400V/3	1,5 kw	18 mm	420 mm	13 m/min	4-6 m³/h	125 kg	Yes	60-68 dB(A)	1010 x 660 x 660 mm
CP 428 S2i	400V/3	3 kw	20 mm	420 mm	12-14 m/min	6-9 m³/h	252 kg	Yes	61-71 dB(A)	1100 x 750 x 800 mm
CP 430 S2i	400V/3	4 kw	20 mm	420 mm	14-16 m/m	7-10 m³/h	295 kg	Yes	64-78 dB(A)	1100 x 750 x 800 mm
CP 424 Cmi	240V/1	1,1 kw	15 mm	420 mm	12 m/min	-	185 kg	Yes	61-75 dB(A)	1400 x 750 x 800 mm

Cushion Pack Cardboard shredder machines to Create yourself your own Cardboard mats from waste cardboard						TOP SELLER
NEW	Cushion Pack CP 333 Nti S2 - 240 V/0,55 kw version - Table model - Inlet height 12 mm - cuttingwidth 320 mm - Production output 10 m/minute (Small Store)		1	Green	1754,50	
NEW	Cushion Pack CP 316 S3i - 240 V/0,75 kw version - Floor model - Inlet height 15 mm - cuttingwidth 320 mm - Production output 12 m/minute (Top Seller)		1	Green	2530,00	
71000028	Cushion Pack CP 320 S3i - 240 V/0,75 kw version - Floor model - Inlet height 15 mm - cuttingwidth 320 mm - Production output 12 m/minute (Top Seller)		1	Green	3080,00	
71000027	Cushion Pack CP 422 S2i S3i - 240 V/1,5 kw version - Floor model - Inlet height 18 mm - cuttingwidth 420 mm - Production output 13 m/minute (Middle company)		1	Green	5225,00	
NEW	Cushion Pack CP 422 S2 - 400 V/1,5 kw version - Floor model - Inlet height 18 mm - cuttingwidth 420 mm - Production output 13 m/minute (Middle company)		1	Green	5225,00	
NEW	Cushion Pack CP 428 S2i - 400 V/3 kw version - Floor model - Inlet height 20 mm - cuttingwidth 420 mm - Production output 14 m/minute (Heavy duty)		1	Green	6820,00	
NEW	Cushion Pack CP 430 S2i - 400 V/3 kw version - Floor model - Inlet height 20 mm - cuttingwidth 420 mm - Production output 16 m/minute (Heavy duty)		1	Green	8360,00	
NEW	Cushion Pack CP 424 Cmi "Chipmaker" Floor model - Inlet height 15 mm - cuttingwidth 420 mm - Production output 12 m/minute		1	Green	6930,00	
NEW	Mobile 100 dust extraction device		1	Green	770,00	

etilux
SMART CONNECTIONS

HEAD OFFICE Rue de l'Espérance 42 • 4000 LIEGE • BELGIUM
T +32 (0)4 224 99 99 • F +32 (0)4 226 11 06 • M info@etilux.be
LUXEMBOURG T +352 266 243-1 • F +352 266 243-43 • M info@etilux.lu



LABELLING & MARKING • TRACEABILITY SOLUTIONS • ADHESIVES & PACKING • AUDIOVISUAL SOLUTIONS