



United Barcode Systems  
Labeling, Coding & Marking

HRX

*The right choice*



# APLINK HRX SERIES

HIGH RESOLUTION INKJET



## HMI DISPLAY 7" or 10"

For a greater comfort, it is possible to remove the controller from the printer's body and place it anywhere on the production line.



## ESCALABILITY

Connect 4 printheads and control them all through the same HMI Display.

## PERIPHERAL CONNEXIONS

Connect encoders, beacons or UVLED curing lamps; link printers or communicate APLINK HRX Series with any item in the line.

## BOTTLE DETECTION SYSTEM

Protects the printhead by preventing errors in changing ink type or ink color and showing ink expiration date warnings.

## PRINTING ON ANY SURFACE

UVLED Curing System configurable through HMI display.



## GRAYSCALE PRINTING

Take coding to the next level with GrayScale printing.

**GS05**  
Up to 3 levels

**GS10**  
Up to 7 levels

## RESOLUTION


Multichannel vertical resolution management and up to 1440dpi of horizontal resolution for a higher contrast.

## CONTRAST PER ELEMENT

Regulates the contrast applied to each element, making it possible to highlight some areas of the message more than others.

## FLEX INTEGRATION SYSTEM

Innovative design that allows the head to rotate on its 3 axes to print in SIDE, TOP or TILT position (from 0° to 90°) fast and easy.



# APLINK HRX SERIES: CODING TAKEN TO THE NEXT LEVEL

APLINK HRX Series is United Barcode Systems’ new generation of high-resolution GrayScale inkjet printers designed to improve coding performance on porous and non-porous surfaces.

PRINTER FEATURES	
PRINTING HIGHT	Up to 72 mm (2,83")
PRINTING SPEED	Up to 250 m/min*
PRINTING CAPACITY	Up to 30 prints/second*
RESOLUTION (VERTICAL / HORIZONTAL)	GS10: from 90dpi to 360 dpi (vertical), up to 1440dpi (horizontal) GS05: from 90dpi to 180dpi (vertical), up to 1440dpi (horizontal)
MESSAGE LENGTH	Max. 50 m
BARCODES	GS1 (GTIN13, GTIN14, GS1-128, GS1 Datamatrix, etc.)
DATA	Texts, variables, formulas, logos, images, dates, etc.
PRINthead POSITION	Side, top or tilt from 0° to 90° (Flex Integration System)
OPTIONS AND ACCESORIES	UVLED Curing System, external beacon, encoder, HMI 10"

HMI FEATURES	
DISPLAY	7" color touchscreen 10" color touchscreen (optional)
PRINthead CONTROL	HMI7" – up to 2 printheads / HMI 10" – up to 4 printheads
COMMUNICATION	USB 2.0, Ethernet, I/O (12)
MESSAGE DESIGN SOFTWARE	UBS Designer Lite and UBS Designer Pro, NiceLabel, Codesoft, Windows Driver

## EQUIPMENT CERTIFICATES



## INK CERTIFICATES



Due to our continuous improvement policy, our product specifications are subject to change without notice.  
\*Maximum speeds and cadences will depend on the design of the message and the elements that make it up.