



HEICO-TEC® TENSION BOLT AND MULTI-TOOL

HEICO-TEC® TENSION BOLT

For applications where the use of a tension nut and shaft is not possible due to lack of available space, we also offer our HEICO-TEC® Tension Bolt. This product is designed with a head diameter that is no larger than that of a standard hex nut ensuring its suitability for tight installation spaces.



HEICO-TEC® MULTI-TOOL

HEICO-TEC® Tension Nuts can be tightened and untightened by hand due to manageable torque values of the many small pressure bolts. That's what makes the application easy, reliable and safe. Especially for the installation of HEICO-TEC® Tension Nuts in serial production environments, HEICO developed the HEICO-TEC® Multi-Tool. Using the HEICO-TEC® Multi-Tool the pressure bolts of the HEICO-TEC® Tension Nut can be tightened with little manual effort of the worker – easy as simply pushing a button.

Advantages:

- Pressure bolts are tightened with the same torque, so there is no manual control with a torque wrench required.
- Effortless attachment thanks to spring-loaded sockets.
- Existing hydraulic units can easily be used without problems.
- For optimizing factory series production.



Scan the QR code for more information on the functional principle of the HEICO-TEC® Multi-Tool.



The HEICO-TEC® Multi-Tool is offered on a project basis. Each tool is designed and constructed for the customer's application. We would be happy to advise you and give you detailed information on the ordering process.