



12 MONTHS WARRANTY







Paint industry Chemical industry Mineral industry Paper industry



HEAVY DUTY SEAL

PARAMETERS

- Max. sealing pressure _____vacuum to 1 bar (15 psi)
- Max. shaft speed______3 m/s (10 f/s)
- PH 0-14
- Max Temperture_____120°C (248°F)
- Max radial runout______0.5mm (0.02")

Consult Tamar for parameters that exceed the range above

Features

MTZ 510-RM provides solution for wet or dry process side entry mixers.

The MTZ 510RM can handle any process and provides 3-4 weeks notification before maintenance.

- Optional split cartridge type simple and easy installation
- Can be serviced while the equipment is running, no downtime
- Simple to install and maintain
- Average life before servicing-2 years

Seal options



Standard dimensions for typical applications



Split seal arangment for large shaft diameter



Air flushed seal for sanitary or high-pressure applications



Unique "floating seal" design for high run-outs

SUCCESS STORY

Application and Issue:

- The customer has several side entry mixers for sugar molasses
- The mixers were previously sealed by packing
- The customer had constant leaks due to run-outs
- The sugar molasses is very thick, hard to mix and harder to clean
- The large shaft (200mm-8") necessitated a splite design

The solution:

TAMAR 510-RM seal:

- No faces or springs to damage
- Splite seal design for fast installation and repair
- Life expectance of min.3 years



The result:

The seal works perfectly for over **1 years**, additional seals were installed and the floor is **clean!**

No leakage No maintenance NO down time





Reliable | Smart | Simple Patent No: 8,215,643 B2

TAMAR SEAL RANGE



410-SF Screw Conveyors



420-VD Vacuum dryers



430-RV Rotary valves



440-PM Packing machines



450-SP Screw pumps



510-RM Ribbon mixer



610-AG Agitators



620-BL Blowers



710-SP Slurry pumps



720-PP Process pumps



730-TP Turbine pumps



740-PC Progressive cavity pumps

Your local TAMAR distributor:



Noordervaartdijk 3 1561PS Krommenie

Tel: +31 (0) 75 6287855
Email: Info@klinkenbergbv.nl
Web: www.klinkenbergbv.nl
www.tamar-tech.com