Compost turner CMC ST 230





The new **CMC ST 230** offers high performance with compact design. The machine creates perfect mixing and ventilation results for tractors of minimum 30 hp. With a net tunnel opening of 2.3 m the machine can turn compost windrows up to a width of 2.6 m. Built on a trailer, in the proven system, the machine

offers all the advantages of its bigger brother such as the side-pull stabilisation, quick coupling and decoupling and it is easily transportable.

The CMC ST 230 corresponds to the strict criteria of Controlled Microbial Composting.





Compost turner



CMC ST 230

Technical data

Maximum width: 2.70 m Maximum height: 1.25 m

Rotor length: 2.30 m

Transport height: 3.55 m

Transport weight: ~ 1.40 t incl. counter weight: ~ 3.40 t

PTO: Bondioli

Standard: 12.5/80-15.3 Tyres: Optional: 400/60-15.5

Grey / Blue Color:

Tractor power: from 30 hp Turning quantity: up to 600 m³/h

Working speed:

100 - 750 m/h (depending on windrow size, density, process progress) **Options:**

Hydraulic pusher axle

Hydraulic front shovels

Hydraulic rotor drive

Stainless steel rotor tunnel

Inoculation system

Special colours

Irrigation boom


1,000 | Irrigation-Inoculation combi


Lighting system 12 V


Brake system

Towing hitch above PTO

Fleece roller







All information is subject to change without notice. Printing errors reserved.