ELAM SOLUTIONS SMACO 5

SMART CORDLESS SCREWDRIVER

Kostengünstige Schraubtechnik, volle Anbindung

WIRELESS LAN

LI-ION BATTERY

OPEN PROTOCOL

Sie wollen Ihre C-Verschraubungen erfassen und dokumentieren, sowie Ihre Schraubsicherheit drastisch erhöhen? Aber herkömmliche Schraubtechnik ist Ihnen zu teuer? Wir haben die Lösung: Der ELAM Solutions Smart Cordless Screwdriver!

Mit einem Drehmomentbereich von ca. 0,3 bis 2,9 Nm, einstellbar in 21 Stufen, eignet sich der handliche Schrauber perfekt, um Verschraubungen der Kategorie C (VDI 2862) auszuführen. Der Open-Protocol konforme Schrauber ist kompatibel zu ELAM Enterprise und ELAM Solutions und dokumentiert die Durchführung. Er kann kabellos über WLAN gesperrt und freigegeben werden und meldet Verschraubungen. Das 2-Gang Getriebe ermöglicht Leerlaufdrehzahlen von 600 oder 200 Umdrehungen/min. Die RGB Indikatorlampe gibt Ihnen eine Rückmeldung über den Zustand des Schraubers und dank zwei mitgelieferten Lithium-Ionen-Akkus, sowie einer Ladestation ist der Schrauber immer einsatzbereit.

Technische Details

Gewicht inkl. Akku	0,54 kg
Produktabmessung (L x B x H)	115 x 125 x 64 mm
Maße gefaltet (L x B x H)	218 x 44 x 142 mm
Akkuspannung	7,2 V
Leerlaufdrehzahl	0-200 / 0-650 min-1
Drehmoment	0,3 - 2,9 Nm
Drehmomenteinstellungen	21
Akkutyp	Li-Ion
Aufnahme	1/4“
Schalldruckpegel (LpA)	70 dB(A)

Armbruster Engineering GmbH & Co. KG

Neidenburger Straße 28
28207 Bremen

Telefon: +49 (0) 421 20 24 8-0
info@armbruster.de
www.armbruster.de

ELAM SOLUTIONS SMACO 5

SMART CORDLESS SCREWDRIVER

Cost-effective screw technology, full connection

WIRELESS LAN

LI-ION BATTERY

OPEN PROTOCOL

Do you want to record and document your C-fasteners and drastically increase your fastening reliability? But conventional screwdriving technology is too expensive for you? We have the solution: The ELAM Solutions Smart Cordless Screwdriver!

With a torque range of approx. 0.3 to 2.9 Nm, adjustable in 21 steps, the handy screwdriver is perfect for carrying out category C (VDI 2862) screw connections. The Open Protocol-compliant screwdriver is compatible with ELAM Enterprise and ELAM Solutions and documents the process. It can be locked and unlocked wirelessly via WLAN and reports screw connections. The 2-speed gearbox enables idle speeds of 600 or 200 rpm. The RGB indicator light gives you feedback on the status of the screwdriver and thanks to the two lithium-ion batteries and charging station supplied, the screwdriver is always ready for use.

Technical details

Weight incl. battery	0.54 kg
Product dimensions (L x W x H)	115 x 125 x 64 mm
Folded dimensions (L x W x H)	218 x 44 x 142 mm
Battery voltage	7.2 V
Idle speed	0-200 / 0-650 min-1
Torque	0.3 - 2.9 Nm
Torque settings	21
Battery type	Li-Ion
Inclusion	1/4“
Sound pressure level (LpA)	70 dB(A)

Armbruster Engineering GmbH & Co. KG

Neidenburger Straße 28
28207 Bremen

phone: +49 (0) 421 20 24 8-0
info@armbruster.de
www.armbruster.de