



Wall Hinge Housing

Series PERLE-ABS

TECHNICAL FEATURES

• OPERATING TEMPERATURE	-40°C...+80°C
• MATERIAL	ABS
• PROTECTION DEGREE	IP67
• IMPACT RESISTANCE	IK 10
• FLAMMABILITY	UL 94 HB
• COLOUR	RAL 7035 Light grey

• SET CONSISTING OF

- Base
- Cover with PUR seal
- Mounting screws
- Internal hinge

• APPROVAL



This wall cabinet housing made of ABS is suitable for both indoor and outdoor use. It is easy to use and very quick to install.

Due to its 30% thicker outer walls the housing has a high impact resistance of IK10. In addition the housing has a high water and dust proof performance of IP 67.

This series is a cost-effective alternative to all sheet steel wall cabinets.



FLANGE PLATES

The enclosures are equipped with knock-outs for cable flange plates.

This allows the cables to be mounted separately from the enclosure.





INTERNAL HINGES

The enclosures of the Perle-ABS series offer internal hinges that are maintenance- and wearfree. The hinges provide optimum user comfort and save time and space.



DIMENSIONS

MODEL	OUTER L x W x H (mm)	INNER L x W x H (mm)	WEIGHT (kg)	FLANGE CONNECTION PRE-STAMPING
BXPFAG360270160-P01	360 x 270 x 160	340 x 250 x 150	2,42	210 x 80 (2x) 290 x 80 (2x)
BXPFAG540270160-P01	540 x 270 x 160	525 x 250 x 150	3,45	210 x 80 (6x)
BXPFAG540360160-P01	540 x 360 x 160	525 x 345 x 150	4,18	210 x 80 (4x) 290 x 80 (2x)



Breuell Ingenieurbüro GmbH

📍 Grützmühlenweg 46 - 22339 Hamburg

☎ (+49) 040-538092-255

☎ (+49) 040-538092-85

✉ info@boxexpert.de

🌐 www.boxexpert.de

