



Line**LIGHT** Fusion

Integrated signalling

With LineLIGHT Fusion, WERMA offers a fully integrable signalling solution that integrates seamlessly into the complete system. The standardised LinelIGHT modules display all machine statuses as functional and integrated design elements. This transfers all the advantages of signalling in terms of safety, efficiency and productivity into the design of the machine.

The fully integrated solution also supports the hygiene requirements of the production environ-

ment. Precise integration into the machine surface minimises dirt edges, avoids openings and offers a high level of protection against the ingress of dust and liquids.

The homogeneous, full-surface illumination of the LineLIGHT Fusion modules ensures optimum visibility and reliably signals hazards or critical machine states.

LineLIGHT Fusion



Technical Specifications

| | 100 mm | 200 mm | 500 mm |
|------------------------------|--|-------------------|-------------------|
| Dimension (L x H x W) | 145 x 33 x 23 mm | 245 x 33 x 23 mm | 545 x 33 x 23 mm |
| Housing | Aluminium, black | | |
| Lens | PC, transparent | | |
| Fixing | Installation mounting | | |
| Protection rating | IP 65 | | |
| Connection | M12 5-pin | | |
| Colour options | Red, yellow, green, white, blue, violet, turquoise (Multicolour) | | |
| Tone type | Pulse tone | | |
| Sound Output | 85 dB | | |
| Working temperature min./max | -20°C/+50°C | | |
| Voltage | 24 V DC | | |
| With acoustic | | | |
| Clips | 300 100 02 | 300 100 06 | 300 100 10 |
| Tape | 300 100 04 | 300 100 08 | 300 100 12 |
| Current consumption | 110 mA | 165 mA | 325 mA |
| Without acoustic | | | |
| Clips | 300 100 01 | 300 100 05 | 300 100 09 |
| Tape | 300 100 03 | 300 100 07 | 300 100 11 |
| Current consumption | 100 mA | 155 mA | 315 mA |

Individual sizes in 50 mm steps from 100 to 1500 mm possible on request.



Mounting clips

Typical application

For machine and plant manufacturers who want to implement a consistent machine design with an integrated signalling solution for signalling machine statuses on

- machines
- automation systems
- assembly systems
- transport and conveyor belts
- AGVs (automated guided vehicles)
- All other industrial products that have a sheet metal housing



Mounting types

- Screw mounting using clips
- Adhesive mounting using industrial adhesive tape

LineLIGHT Fusion is also available as a segment version. This allows the light pattern to be divided into several sections. With the 200 mm version, either the entire length can be illuminated in a single colour or it can be divided into two 100 mm segments with different colours.

From a length of 300 mm, up to three segments are possible: continuous illumination over 300 mm,

two segments of 150 mm each or three segments of 100 mm each, each of which can also be displayed in different colours.

LineLIGHT Fusion Segment



Technical Specifications

| | 200 mm | 300 mm | 600 mm | 900 mm |
|------------------------------|---|-------------------|-------------------|-------------------|
| Dimension (L x H x W) | 245 x 33 x 23 mm | 345 x 33 x 23 mm | 645 x 33 x 23 mm | 945 x 33 x 23 mm |
| Housing | Aluminium, black | | | |
| Lens | PC, transparent | | | |
| Fixing | Installation mounting | | | |
| Protection rating | IP 65 | | | |
| Connection | M12 5-pin | | | |
| Colour options | Red, yellow, green, white, blue (Multicolour) | | | |
| Colour selection | depends on variant | | | |
| Tone type | Pulse tone | | | |
| Sound Output | 85 dB | | | |
| Working temperature min./max | -20°C/+50°C | | | |
| Voltage | 24 V DC | | | |
| Number of segments | 1-2 | 1-3 | 1-3 | 1-3 |
| With acoustic | | | | |
| Clips | 300 100 66 | 300 100 68 | 300 100 70 | 300 100 72 |
| Current consumption | 170 mA | 220 mA | 380 mA | 545 mA |
| Without acoustic | | | | |
| Clips | 300 100 65 | 300 100 67 | 300 100 69 | 300 100 71 |
| Current consumption | 160 mA | 210 mA | 375 mA | 535 mA |

Sizes 1200 and 1500 mm available on request.

Technical Diagram

