

Company:		Date:	
Street:		Contact:	
Zip Code, City:		Phone:	
		e-mail:	

Project data:

Plant/ project:		Country of destination:	
Place of Installation:	indoor	not heated	
	outdoor	without weather protection	
Ambient temperature [°C]:	 to		
Operating mode:	1-shift operation	2-shift operation	3-shift operation
Power supply:	3x400V, 50Hz		
Control voltage:	24V DC		
ATEX-zones:	inside:	outside:	

Product specification:

Conveying material(s):			
Grain size [mm]:		Moisture [%]:	
Temperature [°C]:		Bulk density [t/m³]:	
Conveying volume [m³/h]:		Conveying capacity [t/h]:	
free flowing	fluidizable	bridging	adherent
abrasive	corrosive	electrically conductive	
Other product properties:			

Device specification:

Conveying height [mm]:		Centre distance [mm]:	
Upstream equipment:		Downstream equipment:	
Conveying rope:	Belt	Chain	
Material:	1.0038	1.4301	1.4571
		product contacted parts	completely
Corrosion protection:	RAL 5010/ DFT 80µm		
	galvanized		
	pickled and passivated	glass bead blasted	
Safety device:			
Level indicator	Tracking control	Rotation monitor	
Drive options:	Revision drive	Frequency converter	
Additional equipment:			
Platform with ladder	 m	Assembly carrier	

Notes:

.....

.....

.....