

MC100

GPIO Terminal Global

 **made
in
Germany**



The MC100 GPIO Terminal Global is equipped with a wide range of analogue inputs and digital in- and outputs.

Node-RED™, a simple graphical programming interface supporting various pre-configured transmission protocols, can be used to forward measured values, meter readings, switching statuses and calculations to inhouse servers or visualization software via LTE mobile networks.


In many cases the MC100 GPIO can be used to replace an under-used but cost-intensive electrical PLC controller while simultaneously functioning as an IoT gateway in a single device.

Key features & functionalities:


- Programmable 4G LTE GPIO Gateway
- Quectel EG21-G module integrated
- Out of the box ready for mobile Internet communication
- OpenWrt 21 based Linux distribution, Kernel 5.4.154, optimized for the ARM-based MC100 Gateway
- Node-RED™ – flow-based programming tool pre-installed
- Supports comprehensive cloud and server protocols
- Configuration via web interface
- Free programmable



4G LTE



Node-RED™




OpenWrt Linux



Cloud-Service



GPS/GNSS



10/100 MBit/s
Ethernet



2in/2out or
4in



8in/8out



2out

MC100 GPIO Terminal Global

Technical Data

General	Description	
Type	Wireless 4G LTE gateway with GPIO interfaces	x
Dimensions (W x H x D)	120 x 75 x 35 mm	x
Weight	approx. 175 g	x
Supply voltage	8 to 30 V DC	x
Operation temperature	-20 °C to +70 °C	x
Housing	Plastic	x
Protection class	IP20	x
Mounting	Wall mounting (DIN rail adapter optional)	x
Wireless module embedded	Quectel EG21-G	x
Mobile		
Supporting networks	LTE FDD: Bands: 1, 2, 3, 4, 5, 7, 8, 12, 13, 18, 19, 20, 25, 26, 28	x
	LTE-TDD: Bands: 38, 39, 40, 41	x
	WCDMA: Bands: 1, 2, 4, 5, 6, 8, 19	x
	WI-FI: 2.4 GHz + 5 GHz	x
	GSM: Bands: 2, 3, 5, 8	x
	GNSS: GPS, GLONASS, BDS, Galileo	x
Transmission rates LTE-FDD	DL/UL max. 150/50 Mbps	x
Transmission rates LTE-TDD	DL/UL max. 130/30 Mbps	x
Transmission rates DC-HSDPA	DL max. 42 Mbps	x
Transmission rates HSUPA	UL max. 5.76 Mbps	x
Transmission rates WCDMA	DL/UL max. 384/384 kbps	x
Transmission rates EDGE	DL/UL max. 296/236.8 kbps	x
Transmission rates GPRS	GPRS DL/UL max. 107/85.6 kbps	x
Antenna connections	SMA (female)	3
Controller, Memory and OS		
Controller	ARM Cortex-A7 NXP i.MX 6 UltraLite, 528 MHz	x
RAM	512 MB	x
Flash	4 GB	x
OS	OpenWrt Linux	x
Programmable	C/C++, Python™, Java™, Node-RED™ or others	x
Interfaces controller board (sides)		
Power	Plug-in screw-type terminal	1
Ethernet	10/100 MBit/s	1
LED 1	Power	x
LED 2 and 3	Free programmable	x
LED 4	GSM	x
SIM	Mini SIM	x
SD card	Micro SD, up to 32 GB (internal)	x
GPS	GPS/GNSS (GLONASS/BeiDou/Galileo)	x
Interfaces extension board (top)		
Digital inputs	Galvanic isolated 0 - 30 V, threshold 6 V	8
Digital outputs	Galvanic isolated solid state relais, 300 mA max	8
Analog inputs current	0 - 20 mA	2/4
Analog inputs voltage	0 - 10 V	2/0
PWM outputs	low-side-switch to GND	2
Other properties		
Configurations	Basic configuration via web interface, SSH	x
Approvals	CE; Country-specific approvals upon request	x
Delivery includes		
Wall adapter	Plastic holder	x
Connectors	WR-TBL Series 361 - 3.81 mm vertical cable entry plug (Würth)	x
Printed documentation	Quick Guide	x

Mistakes and changes are reserved.

MC100 GPIO Terminal Global

Variants / Accessories

Variants		Part No.
MC100 GPIO	2 x 0-20 mA, 2 x 0-10 V	162777
MC100 GPIO	4 x 0-20 mA	162511
Accessories		Part No.
Top-hat rail bracket KIT	for DIN rail mounting	100046
Power supply / Mount Adapter EU	18 W AC/12 V DC 1,5A	100909
Network cable	Cat. 5, 1 m	100810
Data cable	Adapter cable for ASC1, RS232 (SuB D9, female) - 1m - 3pin plug	162500
MiMo wall antenna	5G/4G/MIMO/3G/2G, 2x 2 m RG174, 2x SMA (male)	193600
Portable antenna	GSM/UMTS/LTE/WLAN, SMA (male)	101292
GPS antenna	1575.42 MHz, 2 dBi, 3 m RG174 SMA (male), magnetic	101259

Mistakes and changes are reserved.