

XUM

XUT



Transparent

Fast object detection

# Unveil the unseen and detect the essence of transparency!

## XUM & XUT: Make the invisible visible

### Transparent object detection with or without reflector

When it comes to transparent packaging, we don't want to miss a single detail, do we?

By providing object detection with transparency, **we offer our customers a unique opportunity to showcase their products in the best possible light.** We understand that the visual appeal and clarity of packaging can make a significant impact on consumer perception and purchasing decisions.

Therefore, we leave no stone unturned in ensuring that our transparent packaging is of the highest quality, durability, and aesthetic appeal.

The **XUT Blue Light sensors** are an excellent choice for detecting transparent objects at high speed.

With their advanced technology and **high sensitivity**, these sensors can detect even the most transparent objects without reflectors. The XUM polarized reflex sensors, as a second choice, are providing a higher sensing distance while keeping a high precision in transparent object detection.

Each sensor is also designed for easy installation, and can be set up quickly using the teach button or **IO-Link**. Two format sizes, miniature and sub-miniature make them ideal. For applications where space is limited, such as in packaging or assembly lines. With it's IP69K, it is resistant to water and dust ingress, ensuring reliable operation in harsh environments. the sensors are also Ecolab certified.

This technology easily integrates the perfect **LED emitter, optics,** and signal processing, resulting in superior performance. The Blue Light sensors are highly reliable due to their high-precision background suppression capabilities. Even in the presence of intense or reflective backgrounds, such as reflections from metal machine parts, the detection process remains unaffected. Notably, the Blue Light series offers a compact sensor that stands out in the market for its unique feature: the ability to adjust background suppression using a potentiometer. This feature sets it apart as the only Blue Light sensor with this functionality.



XUT

XUM

ECOLAB®

IO-Link



## Simply easy!

[tesensors.com](https://tesensors.com)
**YAGEO** GROUP  
Brings you

**Telemecanique**  
Sensors

## Benefits

Blue Light sensors are a game-changer when it comes to unveiling the invisible. With their versatile object detection capabilities, they can effortlessly detect a wide range of objects, including **deep black**, reflective, curved, angled, shiny, and even transparent ones.


These sensors are especially ideal for installations in tight spaces, thanks to their performance even with challenging angles.

What sets Blue Light sensors apart is their **process reliability**, achieved through precise transmitting and receiving technology. This reliability surpasses that of red-light sensors, ensuring seamless and dependable operation.


Telemecanique Sensors still offers **reflective light technologies**, which serve as a perfect complement for matte and low-reflective surfaces. These technologies are ideal for detecting fast-moving objects, thanks to their long wavelength and intensity.

These capabilities are especially advantageous in applications requiring extended sensing distances, particularly when **transparent boxes**, such as those used for packaging fruits, need to be accurately detected. These technologies excel in handling intricate object shapes and irregular surfaces, delivering reliable detection even on grooved surfaces. A polarized reflex mode significantly enhances light immunity, providing robust protection against environmental factors and minimizing interference from signals emitted by other sensors.


## Transparent sensors – Red light

	Nominal sensing distance	Switching frequency	Degree of protection	Connector type	Part number IO-Link
	2000 mm	1000 Hz	IP67 / IP69K	M8 connector Metal	XUMTARAYM8
	2000 mm	1000 Hz	IP67 / IP69K	Cable, 2 m, 4-wires	XUMTARAYL2
	2000 mm	1000 Hz	IP67 / IP69K	Pigtail, 150 mm M12	XUMTARAYP015

## Transparent sensors – Fixed Blue Light

	Nominal sensing distance	Switching frequency	Degree of protection	Connector type	Part number
	80mm	1000 Hz	IP67 / IP69K	Cable, 2 m, 4-wires	XUM7ABPXL2
	80mm	1000 Hz	IP67 / IP69K	M8 connector	XUM7ABPXM8
	50mm	1000 Hz	IP67	Cable, 2 m, 4-wires	XUT7ABPXL2
	50mm	1000 Hz	IP67	Pigtail 200 mm M8	XUT7ABPXP02

## Transparent sensors – Adjustable (teach button) Blue Light sensors

	Nominal sensing distance	Switching frequency	Degree of protection	Connector type	Part number IO-Link
	80mm	≤ 700 Hz	IP67 / IP69K	M8 Connector Metal	XUM8ABAYM8
	80mm	≤ 700 Hz	IP67 / IP69K	Pigtail 150 mm M12	XUM8ABAYP015
	50mm	≤ 700 Hz	IP67	Cable, 2 m, 4 pins	XUT8ABAYL2
	50mm	≤ 700 Hz	IP67	Pigtail 200 mm M8	XUT8ABAYP02

## Transparent sensors – Adjustable (potentiometer) Blue Light sensors

	Nominal sensing distance	Switching frequency	Degree of protection	Connector type	Part number
	1200mm	600 Hz	IP67 / IP69K	M12 connector / 4 pins	XUK8ABPXM12

## Transparent sensors - Plastic cylindrical

	Nominal sensing distance	Switching frequency	Degree of protection	Connector type	Part number
	1400mm	1000 Hz	IP65 / IP67K	Cable, 2 m	XUBTAPSNL2
	1400mm	1000 Hz	IP67 / IP67K	M12 connector	XUBTAPSNM12

## Transparent sensors - Stainless steel cylindrical

	Nominal sensing distance	Switching frequency	Degree of protection	Connector type	Part number
	1400mm	1000 Hz	IP65/IP67/IP69K	Cable, 2 m	XUBTSPSNL2
	1400mm	1000 Hz	IP65/IP67/IP69K	M12 connector	XUBTSPSNM12

Discover our complete offer: [www.telemecaniquesensors.com](http://www.telemecaniquesensors.com) or contact your local sales agency

### TMSS France SAS

Share capital: 366 931 214 euros  
2 Avenue Gambetta - Tour Egho  
92400 Courbevoie  
908 125 255 RCS de Nanterre  
[www.telemecaniquesensors.com](http://www.telemecaniquesensors.com)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. As standards, specifications and design change from time to time, please ask for confirmation of the information given in this publication. Neither TMSS France nor any of its subsidiaries or other affiliated companies shall be responsible or liable for misuse of the information contained in this document.

Telemecanique™ Sensors is a trademark of Schneider Electric Industries SAS used under license by TMSS France. Any other brands or trademarks referred to in this document are property of TMSS France or, as the case may be, of its subsidiaries or other affiliated companies. All other brands are trademarks of their respective owners.

As standards, specifications and design change from time to time, please ask for confirmation of the information given in this publication

01/2024 TESELEA000073EN

© 2024, TMSS France, All Rights Reserved