

EASY OPEN LINE CRATES

EASY BOX STANDARD

NO NAILS, NO SCREWS



The remarkably light, stackable Easy Box Standard is ideal for packaging larger items. The OSB packing boxes can be adapted individually to match the size of their contents.

The Easy Box Standard stands out for its lightweight design and simple assembly – no nails required. Its sides can be removed effortlessly, with no levers needed. Each box can also be custom-made at no extra cost. The multi-use Easy Box Standard can be sized to fit your products precisely, eliminating wasted space. A seal on the joints provides a clear indication if the box has been opened.



EASY BOX STANDARD

EASY BOX STANDARD		Easy Box Standard	Easy Box Standard+
Fastening system		Slot-together with wooden sections	Slot-together with wooden sections
Contents	Max. length	4820	5820
	Max. width	1820	2320
	Max. height	1870	2370
	Max. weight in kg	≤ 500	> 500
Maximum external container dimensions	Max. length	5000	6000
	Max. width	2000	2500
	Max. height	2000	2500
Material and material thickness – sides & lid	Material, sides	OSB	OSB
	Material thickness, sides	12	12
	Wooden brace, sides	-	Optional
	Additional security with screws	Optional	Optional
	Material lid	OSB	OSB
	Material thickness, lid	12	12
	Wooden brace, lid	-	-
	Lid fastening	Plastic or steel strap	Gaffer tape
	Additional security with screws	Optional	Optional
	Edge protection	-	Optional
Base	Design	Transverse skids	Transverse/longitudinal skids Pallet base
	Pallet base	-	Available from length 850 mm and width 800 mm
	Material	Plywood	Solid wood
	Thickness (mm)	up to 25	up to 50
	Cross skids (mm)	100 × 100	100 × 100
	Longitudinal skids (mm)	-	100 × 100
	Top (mm)	-	100 × 100
	Steel cables	-	Optional
Markings and certifications	Fragile (glass symbol)	Standard	Standard
	Top (arrow symbol)	Standard	Standard
	Keep dry (umbrella symbol)	Standard	Standard
	ISPM 15	Standard	Standard
	Easy Open Line™ (Logo)	Standard	Standard
	Centre of gravity	Optional	Optional
	Do not roll	Optional	Optional
	Do not use forklift	Optional	Optional
	Attach here	Optional	Optional
	Weight limit for stacked load	-	Optional
	Stacking limit	-	Optional
	ISTA 3E load and stability test	Available	Available
Recommended minimum storage requirements	Outdoors	Possible, covered with Valeron film	Possible, covered with Valeron film
	Outdoors, covered	Yes	Yes
	Indoor warehouse	Yes	Yes
	Warehouse with climate control	Yes	Yes
Delivery time from order		48 hours	48 hours

Note: dimensions in mm; weight and load specifications in kg