

Multiline Checkweigher Station



GMP Compliant

Up to 600 pcs/min

High Performance



One of the most difficult quality control steps, precise weight measurement, is now a critical procedure in many sectors. It is crucial for both the manufacturer and the consumer that the precise weight matches the weight on the packaging or the information about the product's completeness. Because products with missing quantities or packing components will result in penalties, while products with excess quantities will result in losses for the manufacturer.

The MCW-100 Multiline Checkweigher was created by VISIOTT professionals to improve the effectiveness of quality control procedures in a variety of industries, including the food, pharmaceutical, and cosmetics sectors. It contributes to "fast manufacturing," which is a critical benefit for businesses today, by weighing 600* goods every minute with an accuracy of 0.1 grams. The measurement range of 5 g to 1000 g makes it a creative option for many different businesses and thousands of different product types.

The MCW-100 Multiline Checkweigher's dual conveyor enables it to simultaneously weigh many products precisely while measuring rapidly. You can effortlessly control the station on a single screen with its user-friendly interface, and you can quickly obtain the operation statistics.

The MCW-100, which separates products outside the specified weight range from the line without slowing down thanks to the reject mechanism, ensures the continuity of quality in production. According to the needs of the business, the VISIOTT Multiline Checkweigher can be modified.


Features

- It can measure the weight of 600(*) products per minute.
- It measures products from 5 g to 1000 g with an accuracy of 0.1 g.
- Easy to integrate into production lines.
- There is a specially designed reject mechanism and a locked reject box.
- It has a touch screen and a user-friendly interface.
- Two channels are managed on a single screen.
- GMP complies with GAMP 5 and 21 CFR Part 11.


Technical Details

Measuring Range	5 g - 1000 g
Accuracy	±0.1 g
Repeatability	0.1 g
Capacity (max)*	600 pcs/minute
Product Length Contol	Yes
Voltage / Frequency	110 V / 220 V / 50 - 60 Hz
Dimensions (WxLxH)	867×1410×1720 mm
Material	Stainless Steel
Computer	Fanless Industrial Computer**
Monitor	Touch Screen Industrial Monitor
Reject Mechanism	Piston
OIML, MID Compliance	Yes
GAMP5 Compliance	Yes
21 CFR Part 11 Compliance	Yes
Customization Options	Extra input-output conveyors, belt weighing conveyor
UPS	Optional
WiFi	Optional

Front View



Top View





GERMANY HQ

4th Floor, Konigsallee 92A 4 0 212 Dusseldorf GERMANY P: +49 2 11 54 039 531 TURKEY HQ **DEMPA Sanayi Sitesi**

3797 Sokak No:22 0610 5 Yenimahalle An kara, TURKEY P: +90 312 386 06 75

