



LINEA INVI PRISMATIC

TRACK LIGHTING

made in
HOLLAND

AVAILABLE IN

Standard	Reflector	Led module	Mounting	Dim options
Dimmable	Reflector	Standard	3-phase	Dimmable
				

Lumen output

Linea60 invi: 2400lm

Linea100 invi: 3600lm

CRI

>90Ra

CCT

2700K • 3000K • 4000K

FIXTURE SPECIFICATIONS

 [View product on website](#)

Fixture weight:



* Linea Invi is exclusively applicable for Powergear® 3-Circuit Track Systems



FIXTURE VARIATIONS

LED module	Lumen	Light colour	Efficiency (Lm/W)	Power	Dim options
SMD 2835 LED 60cm	2400lm	927 / 930 / 940	120	20.0W	Triac / DALI
SMD 2835 LED 100cm	3600lm	927 / 930 / 940	120	30.0W	Triac / DALI

Fixture variations:
¹⁾ Lumen output of LED module (COB) is displayed as net lumen and is subject to 10% tolerance of real time light output (set by international standards)
²⁾ Colour temperature notation is composed of CRI value, indicated by the first digit, and CCT in Kelvin, indicated by the following 2 digits. Accuracy of the Correlated Colour Temperature (CCT) is subject to a tolerance of up to +/- 150 Kelvin compared to nominal value.
³⁾ Fixture efficiency is displayed in lumens per watt and is calculated based on the net lumen output and power consumption of both the LED module and driver.
⁴⁾ Mentioned wattage applies for the total power consumption of the fixture, including both LED module and driver.

Technical data can be changed by Internova Professional Lighting BV without prior notice.

ARTICLE CODE CONFIGURATOR

IN

FIXTURE LENGTH

LIGHT COLOUR

REFLECTOR

FIXTURE COLOUR

DIM OPTIONS

STANDARD

LUMEN OUTPUT

Article code configurator:
¹⁾ This configurator may not be compatible with all PDF readers. For an optimal experience, please open this document using Google Chrome